
Release Notes

Here you can find release notes for the following JMP and JMP Live 19 versions:

- [“Release Notes for JMP 19.1.3 and JMP Live 19.5”](#)
- [“Release Notes for JMP 19.1.2”](#)
- [“Release Notes for JMP 19.1”](#)

About New Features, Release Notes, and Security Bulletins

- **New in JMP/New Features** documentation is published with the initial (.0) release of a new version of JMP and describes new or significantly enhanced capabilities introduced in that release. See <https://www.jmp.com/en/support>.
- **Release Notes** are published with subsequent releases of JMP and summarize changes such as new features, improvements, and bug fixes.
- **Security Bulletins** provide information about security-related issues, including identified vulnerabilities, associated risk levels, affected versions, and recommended remediation. See <https://www.jmp.com/en/company/security-bulletins>.

Release Notes for JMP 19.1.3 and JMP Live 19.5

Release Notes for JMP 19.1.3

JMP 19.1.3 is a targeted maintenance release to fix the following issues in JMP, JMP Pro, JMP Clinical, JMP Student Edition, and JMP Live:

- Performance is now improved when you have many Graph Builder windows open for tables with 1000 or more columns.
- JMP no longer quits unexpectedly when saving prediction and interval formulas on a nested, blocked model.
- In Bayesian Optimization:
 - JMP no longer quits unexpectedly when running the startup script if multiple rows (including duplicate rows) are excluded from the middle of the data table.
 - Very large measurement error values are less inflated and more consistent with the expected behavior. For highly noisy responses, measurement error estimates might still appear large; however, the suggested runs remain valid.
- JMP no longer quits unexpectedly when using Select Matching Cells from virtually joined tables.

For information about security fixes, see the [Security Bulletin](#) page for this release.

Release Notes for JMP Live 19.5

This document describes specific updates for JMP Live 19.5:

- [“Installation and Deployment Enhancements”](#)
- [“Post Enhancements”](#)

Installation and Deployment Enhancements

- The installation windows now include an icon that displays build and version information. The version number also appears beneath the JMP Live logo.
- The installer windows now use a new theme, are the same size, and have consistent elements.
- When an installer detects an existing version, it automatically upgrades that version. Uninstalling the existing version beforehand is not required.
- As a best practice, prior to performing an upgrade, it is recommended to take a full database backup, including large objects (BLOBs). This ensures that data can be restored if needed.
- The JMP Live installer now reads existing .env file settings when performing an upgrade or re-install to avoid overwriting existing settings. It preserves comments, white space, line ordering, and additional settings not managed by the installer when modifying .env files. In addition, a backup file is created each time the installer makes a change to the .env files.
- The JMP Live installer performs some additional validation of settings. You might need to modify the default values for the installer to complete successfully.
- Settings in .env files can now be read from external scripts using command substitution, such as `DB_PASSWORD=$(command-to-retrieve-password)`.

- JMP Live now runs Windows services with an updated version of Windows Service Wrapper and provides configuration of service options (user login, restart and failure settings, log file path and rotation) from the JMP Live installer.
- Errors in the .err.log files now have timestamps so that you can correlate errors with issues in other log files.

Post Enhancements

- Admins can now easily find and clean up outdated reports, unused data, empty folders, and empty spaces.
- A new data table can be created directly on JMP Live.
- A new report post can be created directly on JMP Live.
- Simple edits can now be made to data tables directly on JMP Live.
- Reports and data posts can now be duplicated.
- You can now change the ownership of posts. A user can reassign their posts to other users. An admin can reassign any user's posts.
- You can now show report posts in presenter mode, which displays JMP Live reports in full-screen mode. Web browser menus and tools are removed so that the viewer can focus on the report.
- The history of all control chart warnings in a report can now be downloaded.

Release Notes for JMP 19.1.2

JMP 19.1.2 is a targeted maintenance release to fix the following issues in JMP, JMP Pro, JMP Clinical, JMP Student Edition, and JMP Live:

- In Japanese, some instances of *Prob* were incorrectly translated as *p-value*. These instances have been corrected to *probability* or *proportion*.

For information about security fixes, see the [Security Bulletin](#) page for this release.

Release Notes for JMP 19.1

JMP 19.1 is a general maintenance release that contains enhancements and bug fixes applicable to JMP, JMP Pro, JMP Clinical, JMP Student Edition, and JMP Live. Reproducible crashes and numeric issues have been corrected. Applying this maintenance release is recommended for all users.

This document contains the following content:

- [“New Features”](#)
- [“General Improvements”](#)
- [“Statistical Improvements”](#)

New Features

JMP PRO Add-Ins

- The XGBoost add-in supports a new method called LightGBM, which is a gradient boosting method.

JMP PRO Bayesian Optimization

- When you select the Create New Data Table option in the Bayesian Optimization platform, you now have the option to save only the new batch of factor combinations or to also include the training data.
- There is a new option, Save Prediction Formula, that enables you to save a new formula column for each response to the data table. Each new column contains a prediction formula for a response.
- There is a new launch window option called Include Runs that Do Not Conform to Constraints. This option specifies whether to include points that violate the linear constraints in the data table when generating or loading a candidate set.

Control Chart Builder

- The calculation of zones has been updated to account for limits that are asymmetrical. Because the Western Electric Tests depend on the zones, these tests are now available for asymmetrical limits.
- You can now save out or read in By-group identifiers in a limits table.

Fit Model (Generalized Linear Model)

- The new Prediction and Interval Formulas option in the Generalized Linear Model personality of the Fit Model platform enables you to save formula columns to the data table. These columns contain predictions, confidence limits, and prediction limits, and they can be used in the Prediction Profiler.

Fit Model (Standard Least Squares)

- The new Show CV platform preference in the Fit Least Squares platform enables you to view the CV (coefficient of variation) column by default in the REML Variance Component Estimates table.

JMP PRO Functional Data Explorer

- There are additional methods available in the Baseline Correction option in the Data Processing section of Functional Data Explorer. Previously, this option only performed parametric baseline correction using manually specified settings. Now, you can use the statistics-sensitive nonlinear iterative peak-clipping (SNIP) algorithm or the alternating reweighted least squares solution (ARWLS) algorithm to find a baseline function. There is also an option to load a baseline function from the data.

JMP Live

- A Control Chart Builder report with a Local Data Filter can be successfully published to JMP Live and can be triaged on JMP Live.
- By levels now appear prominently in the control chart warning panel.

JSL Functions

- The Polytope Uniform Random function has been renamed to Random Linearly Constrained Uniform. In addition to a new name, the function has additional options that enable you to generate random samples that are subject to cardinality constraints for specified subgroups of variables.

General Improvements

Data Tables

- JMP now enables you to save data tables directly to a SQLite database file. One JMP data table corresponds to one SQLite database file.

JMP Live

- If you have set up a connection to JMP Live, the Publish Report to JMP Public option no longer appears in the File > Publish menu. You can make it appear by selecting Always allow publishing to JMP Public from the JMP Reports preferences.

JSL Functions

- Support for JMP connections to MATLAB has been restored.

ODBC and Oracle Improvements

- Improved performance time when connecting to Oracle to get data.
- To reduce overhead when retrieving database keys, the Set ODBC Primary Key as Link ID preference is now off by default. When a data table is imported, primary keys are not queried unless you enable this preference.
- Query Builder runs faster because it no longer selects the first table when no tables are selected.
- JMP no longer closes unexpectedly when a network drops or a SQL ODBC connection is unavailable.

Samples

- The Analysis script included in the Software Data.jmp and Phone Data.jmp sample data tables has been updated to include the enhanced covering array analysis options.
- The NYC 311 Records.jmp sample data table was updated. Changes include replacing the local data filter with a global data filter, standardizing the capitalization of column names, and updating the filter view.
- In the Penguins.jmp sample data table, in the Species column, "Adelie Penguin" is changed to "Adelie penguin".
- The Tiretread Simulator Latin Hypercube n5.jmp sample data table has been added to the sample data library. This table can be used to simulate product or process optimization using Bayesian Optimization workflows.

Statistical Improvements

JMP PRO Bayesian Optimization

- It is now required that response columns include the Response Limits column property before launching the platform. If you do not set response limits, an alert window is shown after you click OK in the launch window. You can click Add Goals in the alert window to add any missing response limits. The platform must then be relaunched.
- The save options have been updated in the Bayesian Optimization platform. The Save All Model Fits Script option is now located in the Bayesian Optimization Model Summary red triangle menu in the Model Summary tab. The Save Script for Next Iteration red triangle menu option has been removed. You can still save the start-up script by using the option in the Include Options section of the report in the Batch Selection tab.

JMP PRO Fit Model (Causal Treatment)

- In the Causal Treatment personality of the Fit Model platform, specifying a Local Data Filter at launch now adds the filter to the report, ensuring that analyses are reproduced correctly when launched or scripted.
- In the Causal Treatment personality of the Fit Model platform, Automatic Recalc now remains enabled after it is turned on, allowing analyses to update consistently when data changes occur.
- In the Fit Model launch window, the Causal Treatment personality is now unavailable when the response column has an unsupported modeling type. This prevents selection of the personality for response specifications that are not valid.
- In the Causal Treatment personality of the Fit Model platform, the Save Causal Result Columns option now saves result columns to the original data table when By groups are used.
- In the Causal Treatment personality of the Fit Model platform, Relaunch Analysis now behaves consistently with the Model Dialog and Recall options. This enables analyses to be relaunched as expected.
- The Causal Treatment personality of the Fit Model platform now shows separation warnings only when separation is present in the data. This prevents spurious warnings for models without separation.

- When the outcome is binary, the mosaic plot in the Outcome by Treatment report now reflects specified Frequency or Weight variables when they are used in the model.
- The Outcome by Treatment report now scales the vertical axis to the observed data range when all outcome values are positive, or all values are negative, instead of forcing the axis to include zero.
- JMP no longer closes unexpectedly when fitting Causal Treatment models in cases where the treatment model cannot be estimated successfully, such as perfect separation or exceeded parameter limits.
- When the Causal Treatment personality is selected and a model exceeds the parameter limit, which can result in excessive computation time, JMP now shows a warning and does not fit the model.

JMP PRO Fit Model (Mixed Model)

- For mixed models that contain a Weight variable, the degrees of freedom for prediction intervals are now correctly calculated. This applies to models in the Mixed Models and Standard Least Squares personalities of the Fit Model platform.

Fit Model (Standard Least Squares)

- The Method option now appears when you add the Random attribute to an effect in the Fit Model launch window.

Principal Components

- Performance of analyses that use Sparse SVD, such as PCA, has been improved on Windows, restoring expected run times for large or sparse data sets.

JMP PRO Structural Equation Models

- The Cross-Lagged Panel Model shortcut now includes random intercepts correctly when multiple processes are modeled, and the Add Random Intercept option is checked.
- The Measurement Invariance and Multigroup Measurement Invariance shortcuts now work correctly when using the MIIV-2SLS estimator. The strict invariance option (which is not supported with MIIV-2SLS) is no longer available.
- Fixed issues in higher-order models with the MIIV-2SLS estimator, where some equality-constrained parameters were not estimated.
- The MIIV-2SLS estimator now correctly includes manifest-variable mediators as instruments in models with latent-variable outcomes.
- The Latent Scale Set rule now validates mean-structure constraints for higher-order latent factors when using the MIIV-2SLS estimator.
- Saved scripts now correctly recognize variables when column names contain unusual spacing characters.